Refer to Service Bulletin: SB-6-182



CAMAER by DeVilbis

CT Desiccant Cartridge Dryer

Order No. Description

130500 Desiccant Air Dryer wall mount **130501** Desiccant Air Dryer portable with stand

Air Control

Easy Change Desiccant Air Dryer

- CT series desiccant air dryers remove water vapor from the compressed air down to a dew point of -40° F
- Quick change 10 lb. desiccant cartridge bag is made of a special fiber media which removes oil aerosols and solid particles down to 0.1 micron meaning no need for coalescing or final filters
- Install at point of use
- 30 CFM air flow capacity

3 _		Ref. No. Order No. De
" — г		1 130505 H (1
		1 2 130511 D
L		3 130510 G
		*4 130504 D
	Air Out	* The Material Safety
Air Inlet	<section-header><section-header><section-header></section-header></section-header></section-header>	SPECIFICATIONS Air Inlet Air Outlet Air Flow Capacity Maximum Operati Maximum Temper Humidity Indicato Water Vapor Remm Partical Removal Manual Drain
	130500 Dry	er Shown
		- 2
	U	

Ref. No.	Order No. Description		Ind. Parts Req.
1	1 130505 Humidity Indicator (1 Humidity Indicator Paper included)		
2	130511	Drain (Manual)	1
3	130510	Gasket	1
*4	130504	Desiccant Cartridge (not shown)	1

Safety Data Sheet (MSDS-52) is available upon request.

NS

acity perating Pressure mperature licator Removal

200 PSIG (14 Bar) 150°F (65.6°C) Green: OK Yellow: Replace Desiccant -40°F Dew point 0.1 micron Included

½" NPT (Female) ½" NPT (Female) 30 CFM



