



# 

**TRU-CURE IR6LT** 



TC-IR6LT-01 (904112 FOR USA)	TRU-CURE IR6LT (NORTH AMERICA)	
TC-IR6LT-02	TRU-CURE IR6LT (UNITED KINGDOM)	
TC-IR6LT-03	TRU-CURE IR6LT (EUROPE)	



For other languages of this service manual as well as additional product information, please scan the QR code above.

### EC Declaration of conformity

According to testing institutes and according to the machine directive the Trisk Devilbiss products in this manual are not defined as machines, wherefore the machine directive reference cannot be included in this declaration.

In accordance with EN 17050-1:2010

We, Hedson Technologies AB Box 1530 SE 462 28 Vänersborg Sweden

declare under our sole responsibility that the products

Trisk Devilbiss TRU-CURE IR6LT

that are used to accelerate the drying of paint, to which this declaration relates, are in conformity with the following standards

EN 60335-1:2002 +A11+A1+A12 +A2+A13	Specification for safety of household and similar electrical appliances General requirements
EN 60335-2-45:2002 +A1	Specification for safety of household and similar electrical appliances Particular requirements
EN 61000-6-3	Electromagnetic Compatibility, Generic Emission Standard
EN 61000-6-2	Electromagnetic Compatibility, Generic Immunity Standard
EN 61000-3-3	Limitation of voltage fluctuations
EN ISO 9001	Quality Management System
EN61000-3-12	Limits for harmonic current emissions

Compliance statement:

The EN61000-3-2 does not apply to this professional equipment. However it complies to EN61000-3-12 provided that the short circuit power Ssc is greater or equal to 300kVA or that the corresponding short circuit current Isc is greater or equal to 430A at interface point between user and public power system.

In accordance with the provisions of the following directives in their most current version

2014/35/EU	Low Voltage Directive
2014/30/EU	Electromagnetic Compatiblity

Vänersborg, Sweden, March 2023

Linus Ekfeldt Product Company Director IRT

## **Declaration of conformity UKCA**

We, Hedson Technologies AB Box 1530 SE 462 28 Vänersborg Sweden

declare under our sole responsibility that the products

Trisk Devilbiss TRU-CURE IR6LT

that are used to accelerate the drying of paint, to which this declaration relates, are in conformity with the following standards

EN 60335-1:2002 +A11+A1+A12 +A2+A13	Specification for safety of household and similar electrical appliances General requirements
EN 60335-2-45:2002 +A1	Specification for safety of household and similar electrical appliances Particular requirements
EN 61000-6-3	Electromagnetic Compatibility, Generic Emission Standard
EN 61000-6-2	Electromagnetic Compatibility, Generic Immunity Standard
EN 61000-3-3	Limitation of voltage fluctuations
EN ISO 9001	Quality Management System
EN61000-3-12	Limits for harmonic current emissions

Compliance statement:

The EN61000-3-2 does not apply to this professional equipment. However it complies to EN61000-3-12 provided that the short circuit power Ssc is greater or equal to 300kVA or that the corresponding short circuit current Isc is greater or equal to 430A at interface point between user and public power system.

In accordance with the provisions of the following directives in their most current version

Electrical Equipment (Safety) Regulations 2016 Electro-magnetic Compatibility Regulations 2016 The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012

Vänersborg, Sweden, March 2023

Linus Ekfeldt Procuct Company Director IRT

## In this part sheet, the words **WARNING**, **CAUTION** and **NOTE** are used to emphasize important safety information as follows:

## **A WARNING**

Hazards or unsafe practices which could result in severe personal injury, death or substantial property damage.

## 

Hazards or unsafe practices which could result in minor personal injury, product or property damage.

## NOTE

Important installation, operation or maintenance information.

## A WARNING

### Read the following warnings before using this equipment.



#### READ THE MANUAL

Before operating finishing equipment, read and understand all safety, operation and maintenance information provided in the operation manual.



### OPERATOR TRAINING

All personnel must be trained before operating finishing equipment.



#### EQUIPMENT MISUSE HAZARD

Equipment misuse can cause the equipment to rupture, malfunction, or start unexpectedly and result in serious injury.



#### LOCK OUT / TAG-OUT

Failure to de-energize, disconnect, lock out and tag-out all power sources before performing equipment maintenance could cause serious injury or death.



#### AUTOMATIC EQUIPMENT Automatic equipment may start suddenly without warning.

**PRESSURE RELIEF PROCEDURE** Always follow the pressure relief procedure in the equipment instruction manual.



#### **KEEP EQUIPMENT GUARDS IN PLACE** Do not operate the equipment if the safety devices have been

removed.



#### KNOW WHERE AND HOW TO SHUT OFF THE EQUIPMENT IN CASE OF AN EMERGENCY



#### WEAR SAFETY GLASSES

Failure to wear safety glasses with side shields could result in serious eye injury or blindness.



#### INSPECT THE EQUIPMENT DAILY

Inspect the equipment for worn or broken parts on a daily basis. Do not operate the equipment if you are uncertain about its condition.



#### **NEVER MODIFY THE EQUIPMENT**

Do not modify the equipment unless the manufacturer provides written approval.



#### NOISE HAZARD

You may be injured by loud noise. Hearing protection may be required when using this equipment.



#### PINCH POINT HAZARD

under pressure, or flying debris.

PROJECTILE HAZARD

Moving parts can crush and cut. Pinch points are basically any areas where there are moving parts.

You may be injured by venting liquids or gases that are released



#### STATIC CHARGE

Fluid may develop a static charge that must be dissipated through proper grounding of the equipment, objects to be sprayed and all other electrically conductive objects in the dispensing area. Improper grounding or sparks can cause a hazardous condition and result in fire, explosion or electric shock and other serious injury.



#### WEAR RESPIRATOR

Toxic fumes can cause serious injury or death if inhaled. Wear a respirator as recommended by the fluid and solvent manufacturer's Safety Data Sheet.



#### **TOXIC FLUID & FUMES**

Hazardous fluid or toxic fumes can cause serious injury or death if splashed in the eyes or on the skin, inhaled, injected or swallowed. LEARN and KNOW the specific hazards or the fluids you are using.



#### FIRE AND EXPLOSION HAZARD

Improper equipment grounding, poor ventilation, open flame or sparks can cause a hazardous condition and result in fire or explosion and serious injury.



### Any injury caused by high pressure liquid can be serious. If you are injured or even suspect an injury:

MEDICAL ALERT

- Go to an emergency room immediately.
- Tell the doctor you suspect an injection injury.
- Show the doctor this medical information or the medical alert card provided with your airless spray equipment.
- Tell the doctor what kind of fluid you were spraying or dispensing.

#### GET IMMEDIATE MEDICAL ATTENTION

To prevent contact with the fluid, please note the following:

- Never point the gun/valve at anyone or any part of the body.
- Never put hand or fingers over the spray tip.
  - Never attempt to stop or deflect fluid leaks with your hand, body, glove or rag.
  - Always have the tip guard on the spray gun before spraying.
  - Always ensure that the gun trigger safety operates before spraying.

IT IS THE RESPONSIBILITY OF THE EMPLOYER TO PROVIDE THIS INFORMATION TO THE OPERATOR OF THE EQUIPMENT. FOR FURTHER SAFETY INFORMATION REGARDING THIS EQUIPMENT, SEE THE GENERAL EQUIPMENT SAFETY BOOKLET (77-5300).

EN

## **A** DANGER

#### EXPLOSION

To reduce risk of explosion, do not use in paint spray booths or within 10 feet of paint spraying operations.

## 

#### FIRE AND EXPLOSION

Do not use in an area until it is checked and cleared of combustible and/or flammable materials.

Do not use in an area where the air may contain flammable dust, gas, or liquid vapors.

Never direct the heating equipment towards any pressurized vessel.

Never direct the heating equipment towards combustible or flammable materials.

If you have a distance less than 60 cm/2 feet to the object the temperature might raise quickly and the risk for fire increases.

#### **ELECTRICAL EQUIPMENT**

The mobile dryer is operated by highly dangerous electrical voltage.

#### ACCESSING ELECTRICAL EQUIPMENT

Before accessing live parts, remove the main connector from the wall socket. Only professional electricians may have direct access into the electrical equipment.

If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.

#### WARNING!

Intensive heat radiation. Hands, face and other parts of the body should be exposed as little as possible to the heat radiation.

## **A** CAUTION

CAUTION

Hot surface. Avoid contact.

#### FIELD OF APPLICATION

The Trisk Devilbiss IR6LT are designed to provide an accelerated and even cure of most automotive refinishing materials. Typically drying of putty, filler, base and top coats, both water-based and solvent-based products. Its site of use is the preparation area and finishing area. Within the automotive industry and vehicle repair sectors, it is used to dry small areas and cure materials before polishing .

#### **PRODUCT DESCRIPTION**

The easily maneuverable Trisk Devilbiss IR6LT are equipped with both dual and single lamp cassettes for easy adjustment and flexibility around curved parts without sacrifice to heat distribution. The design, combined with a gas spring, makes cassette adjustment simple. The IR lamps and reflectors are protected against mechanical damage with a mesh. The control unit enables flash off (50% power) and full bake (100% power). The time can be set individually for each mode (0-30 min). Additionally, the IR6LT unit is equipped with a contactless temperature control where the temperature can be set between 20°C and 99°C.

#### PARTICULAR ADVANTAGES

#### Unique reflector design

The Trisk Devilbiss IR6LT features a unique dimpled sheet reflector that generates extremely even curing intensity and temperature over entire surfaces. This ensures the fastest possible curing time, while minimizing risk of over-curing or burning sections of your coating.

#### Good maneuverability

The Trisk Devilbiss IR6LT are sized to cure higher surfaces such as hood and roof. Lockable gas piston makes it very easy to set point of parallel arm. IR6LT has a laser guided pyrometer displaying surface temperature readout which make it even easier to properly position the lamps.

#### **TECHNICAL DATA**

Electrical diagram, see page 9.

Rated Voltage	380 V - 420 V 50/60Hz 3 Phase	220 V - 240 V 50/60Hz Single Phase
Rated power	6 emitters Full power 6200W	6 emitters Full power 6200W
Heating elements	6 quartz Tungsten filament Infrared emitters	6 quartz Tungsten filament Infrared emitters
Fuse*	16 A	30 A
Noice level	Less than 70 dB (A)	Less than 70 dB (A)
Max ambient temperature during operation	40°C	40°C
Max ambient temperature during storage and transportation	70°C	70°C

\* The dryer must be supplied by recommended fuse.

#### **INSTRUCTION TO THE OWNER**

The owner of the mobile dryer must produce clear operating instructions, adapted to local site conditions and applicable national / regional requirements, and make these available to all users.

Mobile dryer users must adhere to these operating instructions. The mobile dryer user must always ensure that sufficient technical ventilation is complied in accordance with the applicable national / regional requirements.

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. Children should be supervised to ensure that they do not play with the appliance.

Dispose of spent items at the nearest environmental protection facility for recycling.

### **TRU CURE IR6LT – OPERATING INSTRUCTIONS**

#### IR6LT – WITH TEMPERATURE CONTROL

The mobile dryer is equipped with an automatic temperature control. This enables optimum drying/ curing results within the shortest possible time. The temperature control (pyrometer) measures the temperature contactless by optics. The laser pointer indicates where the temperature is measured in the material cured.

The mobile dryer is also equipped with two power levels, flash off (50% power) and full bake (100% power) whith individually timers.

#### **START-UP**

Turn the main switch on. This will initiate the electronics. Four dots will sequentially blink to indicate the start-up. Next the top display will show 1P (1-phase) OR 3P (3-phase). The lower display shows the supply frequency 50 or 60 Hz.

When the start-up sequence is over, the displays show the last used curing values. The upper window shows flash off set time in minutes and the lower window shows the maximum temperatur allowed or full bake set time in minutes. Use the toggle button to alter the lower window beetween maximum temperature or minutes settings for the fullbake. Use alse the toggle button to alter the use of one or two cassettes.

#### SETTINGS

Use the + and - buttons below the displays to change the settings. Use the toggle button to change between maximum temperatur setting and minutes for full bake setting. Pressing the buttons continously will rapidly increase the setting. Each timer can be set between 0 and 30 min and the temperature between 20°C and 99°C. The settings will remain even after power-off and serve as default for the next curing operation.

#### CURING

Start the laser by pressing the On/Off button once. Adjust the cassette so the laser point is visibale on the surface to be cured and temperatur measured. Start the curing by pressing the On/Off button a second time.

The active timer will flash and the heater will switch off automatically when the set times have elapsed. After idling for 30 minutes, the unit enters stand-by mode when a dot in each display flashes. Pressing any button will activate the unit again.

	TRISK DEVILBISS
FLASH OFF TIMER	
FLASH OFF SETTINGS	
FULL BAKE TIMER	ic F
FULL BAKE SETTINGS	
INDICATOR LAMP TEMP/TIME	
TOGGLE BUTTON TEMP/TIME/CASETTE	
ON/OFF BUTTON	
MAIN SWITCH – LOCATED ON THE RIGHT HAND SIDE	

## NOTES

Minimum curing distance is 50 cm and optimal curing distance is 60 cm.

The pyrometer measure the temperature at a diametar of 10cm around the laserdot.

Make sure that you don't measure the temperature on glass, tyres or outside the object (10 cm diameter around the laser dot). Otherwise, the result between the programmed temperature values and actual values may differ. This may lead to unsatisfactory results.

The FLASH OFF timer controls the duration of the half power output of the emitters. The FULL BAKE timer controls the duration of the full power output of the emitters. If both FLASH OFF and FULL BAKE timers are used, the FLASH OFF timer will count down first and upon switching off it will engage the FULL BAKE timer automatically.

Alterning between temperature and timer in the lower window is possible even during curing.

To stop the unit before the time is out, press the On/Off button.

If the temperature inside the control unit rises over 65°C (149°F), the unit switches off. The upper display will show Ot (over temperature) and the lower the actual temperature. Automatic reset when the temperature falls below 55°C (131°F) and the unit is ready for operation again.

#### MAINTENANCE

#### LAMP REPLACEMENT

## NOTE

Only use original Trisk Devilbiss lamps with the correct power rating.

- 1. Disconnect power supply.
- 2. Remove the mesh.
- 3. Remove the old lamp.
- 4. Install new lamp in reverse order.

## A CAUTION

Do not touch the new lamp with your fingers. Remove the protective paper on the lamp after you have installed it.

#### TROUBLESHOOTING

PROBLEM	POSSIBLE CAUSE	POSSIBLE SOLUTION
Solvent popping	Unit too close to panel Insufficient flash off time Paint system has fast thinner	Move unit further away Increase flash off time Use a standard or slow thinner
Undercure or softness of the paint film	Unit too far away Insufficient bake time Excessive film weight	Move unit closer Increase full bake time Apply lighter coats
Softness on the edge of repair	Repair too large for I.R. unit	Split area into two, move unit for 2nd application. If flash off is used, it will not be necessary on 2nd application.
Difficulty in polishing out dirt nibs	Too long on bake cycle Unit too close to panel	Reduce cure time Move unit further away

#### **SPARE PARTS**

PICTURE	PART NO.	DESCRIPTION
	410-1000 991000 for USA	1 KW IR QUARTS LAMP
	410-1001 991001 for USA	REFLECTOR
	410-1002 991002 for USA	PROTECTIVE MESH
	410-1003 991003 for USA	1 KW CASSETTE COMPLETE
	410-1030 991030 for USA	2 KW CASSETTE COMPLETE IR6L 3 PHASE (NO TEMPERATURE SENSOR) (EU+UK)
	410-1032 991032 for USA	2 KW CASSETTE COMPLETE IR6L SINGLE PHASE (NO TEMPERATURE SENSOR) (NA)
	410-1031 991031 for USA	2 KW CASSETTE COMPLETE IR6LT 3 PHASE (EU+UK) (WITH TEMPERATURE SENSOR AND LASER POINTER)
	410-1033 991033 for USA	2 KW CASSETTE COMPLETE IR6LT SINGLE PHASE (NA) (WITH TEMPERATURE SENSOR AND LASER POINTER)
	410-1034 991034 for USA	CONTROL UNIT COMPLETE IR6LT (EU+UK)
	410-1035 991035 for USA	CONTROL UNIT COMPLETE IR6LT (NA)
	410-1036 991036 for USA	GAS STRUT 1500 N
FF F	410-1013 991013 for USA	CASTOR
	410-1043 991043 for USA	BRAKE FOR CASTOR (2 PCS)
	410-1037 991037 for USA	CORD SET 5 M 3 PHASE (EU+UK)
	410-1038 991038 for USA	CORD SET 5 M SINGLE PHASE (NA)
	410-1039 991039 for USA	POWER CABLE 0.5 M – CASSETTE TO CASSETTE (EU+UK)
	410-1040 991040 for USA	POWER CABLE 0.5 M – CASSETTE TO CASSETTE (NA)
	410-1041 991041 for USA	POWER CABLE 2.5 M – CONTROL UNIT TO CASSETTE (EU+UK)
	410-1042 991042 for USA	POWER CABLE 2.5 M – CONTROL UNIT TO CASSETTE (NA)
	410-1023 991023 for USA	CONTROL CABLE TEMP/LASER 2.5 M – CONTROL UNIT TO CASSETTE

ELECTRICAL DIAGRAM 230V SINGLE PHASE



### ELECTRICAL DIAGRAM 400V 3-PHASE











413600\_REV1 2023-12-12 MF

### NOTES

#### WARRANTY POLICY

This product is covered by Carlisle Fluid Technologies' materials and workmanship limited warranty. The use of any parts or accessories, from a source other than Carlisle Fluid Technologies, will void all warranties. Failure to reasonably follow any maintenance guidance provided may invalidate any warranty.

For specific warranty information please contact Carlisle Fluid Technologies.

For technical assistance or to locate an authorized distributor, contact one of our international sales and customer support locations.

Region	Industrial / Automotive	Automotive Refinishing	
Amoricas	Tel: 1-800-992-4657	Tel: 1-800-445-3988	
Americas	Fax: 1-888-246-5732	Fax: 1-800-445-6643	
Europe, Africa,	Tel: +44 (0)1202 571 111		
Middle East, India Fax: +44 (0)1.		1202 573 488	
Tel: +8		-3373 0108	
China	Fax: +8621-3373 0308		
_	Tel: +81 4	5 785 6421	
Japan	Fax: +81 45 785 6517		
	Tel: +61 (0)	2 8525 7555	
Australia	Fax: +61 (0)	2 8525 7575	

For the latest information about our products, visit www.carlisleft.com

Carlisle Fluid Technologies is a global leader in innovative finishing technologies. Carlisle Fluid Technologies reserves the right to modify equipment specifications without prior notice.

BGK<sup>™</sup>, Binks<sup>®</sup>, DeVilbiss<sup>®</sup>, Hosco<sup>®</sup>, MS<sup>®</sup>, and Ransburg<sup>®</sup> are all registered trademarks of Carlisle Fluid Technologies, LLC.

©2024 Carlisle Fluid Technologies, LLC. All rights reserved.



16430 North Scottsdale Rd., Suite 450 Scottsdale, AZ 85254 USA