

13-0041 (HAF-500) 100 CFM AIR CONTROL UNIT

DESCRIPTION

This filter unit is designed to remove dirt, pipe scale and most liquid aerosols. Any of these, especially water, may cause severe damage to the paint finish. This unit is rated at 100 CFM.

SPECIFICATIONS

Air Inlet	1/2" NPT(F)
Air Outlet	1/2" NPT(F)
Air Capacity	100 CFM
Max. Temperature	150° F
Intermittent To	180° F
Max. Inlet Pressure	150 PSI

INSTALLATION

WARNING

Risk of personal injury.
 Risk of property damage.

Except as otherwise specified by the manufacturer, this product is specifically designed for compressed air service and use with any other fluid (liquid or gas) is a misapplication. For example, use with or injection of certain hazardous gases in the system (such as oxygen or liquid petroleum gas) could be harmful to the unit or result in a combustible condition that may cause fire or explosion. Manufacturer's warranties are void in the event of misapplication and manufacturer assumes no responsibility for any resulting loss.

WARNING

Risk of injury. Do not place unit in service without metal bowl guard installed. Plastic bowl units are sold only with metal bowl guards. To minimize the danger of flying fragments in the event of plastic bowl failure, guard must not be removed. If the unit is in service without the metal bowl guard installed, manufacturer's warranties are void and the manufacturer assumes no responsibility for any resulting loss. If unit has been in service and does not have a metal bowl guard, order one and install before placing back in service.

Figure 1

