

# 2-Stage Filter System

Order No. **130523** 

# 3-Stage Filter System

Order No. 130526










## **CamAir Filter Systems**

Ord	er No.	escription	
130	523	2-stage filter unit with regulator	
130	526	3-stage filter unit with 2 regulators	

### Flow vs Pressure Drop of 130523 2-Stage Filter Unit




## Air Filtration/Regulation Systems

- Compact and effective—perfect for cramped shop spaces
- · Removes dirt, water and oil from air lines to 0.01 micron—assures superior finishes
- · Quick change bowls and air inlet valve accommodate rapid, trouble free maintenance without shutting off main shop air
- Combine 2-stage filter with the CT-30 desiccant dryer to create a CT Plus 5-stage filter system
- 65 SCFM @ 90 PSIG

Refer to Service Bulletins and Instructions: SB-6-182, SI-6-18-8, SI-6-18-10

### 130523 2-Stage w/Regulator



# 2-Stage Filter Set Parts

Ref. No.	Part No.	Description	Ind. Parts Req.
1	130519	Drain Kit (1 set)	1
2	130517	Filter Element, Water	1
3	130518	Filter Element, Coalescing	1
4	130520	Indicator Kit, Coalescing	1
5	VA-595	Shut-off Valve	1


2-STAGE FILTER SPECIFICATIONS Air Flow 65 SCFM @ 90 PSIG Max. Pressure 150 PSIG Max. Temperature 150°F

REGULATOR SPECIFICATIONS
Air Flow 65 SCFM @ 100 PSIG Max. Inlet Pressure 250 PSIG Regulated Pressure Range 2–125 PSIG Max. Temperature

## 2-Stage Regulator Parts

Ref. No.	Part No.	Description	ind. Parts Req.
1	130521	Regulator Kit	1
2	VA-594	Shut-off Valve	1
3	GA-288	Gauge	1

## 130526 3-Stage w/Regulators



# 3-Stage Filter Set Parts

Ref. No.	Part No.	Description	Parts Req.
1	130519	Drain Kit (1 set)	1
2	130517	Filter Element, Water	1
3	130518	Filter Element, Coalescing	1
4	130520	Indicator Kit, Coalescing	1
5	VA-595	Shut-off Valve	1
6	130527	Filter Element, Charcoal	1

## **3-Stage Regulator Parts**

Ref. No.	Part No.	Description	Ind. Parts Req.
1	130521	Regulator Kit	1
2	H-2008	Adapter	1
3	GA-288	Gauge	1
4	GA-375	Gauge, Upside Down	1
5	VA-594	Shut-off Valve (optional)	1

